

# GFM-C Series

## 6GFM-50 12V50Ah

GFM-C series VRLA battery uses latest AGM technology, high purity raw materials and many patented technologies that ensure its long floating and cycle life, it is applicable to less frequency of power failure, and shallow discharge of depth site. It is mainly used for indoor telecommunication base station.

### Benefits

- Long life according to EUROBAT Classification
- High discharge performance
- 99%+ gas recombination efficiency
- Maximum charge efficiency
- Low self-discharge rate
- Vertical installation


### Applications

- Telecommunications
- Power system
- UPS
- Emergency power

### Standards

- IEC 60896-21/22
- JIS C8704-1/2
- EUROBAT guide

### Drawing



### Specifications





Battery Model	6GFM-50			
Design Life (years, 25°C)	10			
Capacity (Ah, 25°C)	10HR (5A, 1.80V)	5HR (8.48A, 1.80V)	3HR (12.5A, 1.80V)	1HR (27.5A, 1.75V)
	50	42.4	37.5	27.5
Dimensions (mm)	Length	Width	Height	Total Height
	258	168	169	177
Approx. Weight (kg)	16.6			
Reference Internal Resistance (mΩ)	6.8 ( fully charged @ 25°C)			
Maximum Discharge Current (A/1 Sec.)	400			
Self-Discharge (25°C)	≤ 2% per months			
Charge Voltage (V/cell, 25°C)	Cycle use		Float use	
	2.35(-3.5mV/°C/cell), max charge current: 12.5A		2.25(-3.5mV/°C/cell)	
Short Circuit Current (A)	1750			

## Discharge Data

Constant Current Discharge Data (25°C, A)																
End Voltage (V/cell)	min							h								
	5	10	15	20	30	40	50	1	1.5	2	3	4	5	6	8	10
1.60	168.2	124.0	100.1	83.01	56.72	43.58	35.65	31.03	23.09	18.51	14.01	11.14	9.41	8.01	6.31	5.27
1.65	154.3	117.0	94.71	78.54	55.02	42.27	34.58	30.03	22.59	18.10	13.61	10.89	9.16	7.85	6.21	5.22
1.70	141.8	109.3	88.55	73.30	53.36	41.01	33.54	28.53	22.02	17.63	13.26	10.54	8.93	7.70	6.11	5.15
1.75	128.6	101.6	83.01	69.45	51.77	39.77	32.53	27.50	21.59	17.16	12.85	10.21	8.70	7.51	6.01	5.08
1.80	118.6	96.3	78.58	65.80	50.20	38.58	31.55	26.60	21.04	16.60	12.50	9.981	8.48	7.31	5.89	5.00

Constant Power Discharge Data (25°C, W/cell)																
End Voltage (V/cell)	min							h								
	5	10	15	20	30	40	50	1	1.5	2	3	4	5	6	8	10
1.60	281.1	215.8	173.2	142.7	101.9	82.9	68.5	58.9	44.30	35.94	26.38	21.19	18.83	15.86	12.42	10.39
1.65	261.8	203.4	165.7	136.3	98.8	80.1	66.7	57.2	43.21	35.12	25.91	20.81	18.46	15.63	12.32	10.32
1.70	246.4	192.5	156.1	128.9	95.0	77.6	64.7	55.6	42.19	34.38	25.53	20.34	18.10	15.45	12.17	10.24
1.75	225.6	180.8	148.9	123.3	91.2	74.0	62.3	54.2	41.05	33.83	25.04	19.99	17.73	15.24	12.01	10.14
1.80	207.9	167.8	139.8	117.5	87.3	70.5	59.3	52.9	40.26	33.28	24.62	19.66	17.37	15.06	11.89	10.06

## Performance Curve



### Sacred Sun Power Sources Co., Ltd.

Add: No.1 Shengyang Road, Qufu 273100 PRC  
Tel: +86-537-4422313 Fax: +86-537-4411980  
Email: sales@sacredsun.cn

### Sacred Sun Hong Kong Co., Limited

Add: RM 19C Lockhart CTR 301-307 Lockhart RD Wan Chai, Hong Kong  
Email: admin.hk@sacredsun.hk

### Sacred Sun Asia Pacific Pte Ltd.

Add: 1 Ubi View, #04-12, Focus One, Singapore 408555  
Email: admin.sg@sacredsun.sg

### Sacred Sun Europe SARL

Add: ZAE Fontaine, 33210 Fargues, France  
Email: admin.eu@sacredsun.eu

### Sacred Sun MEA FZE

Add: No. 311 office, Building LOB 14, JAFZA, Dubai, UAE  
Email: admin.ae@sacredsun.ae

